

## D150 & D500



- CLASS D TRANSFORMERLESS AMPLIFIERS
- V2000 AMPLIFIER MAINERAME COMPATIBLE
- SOFTWARE CONFIGURABLE MAXIMUM POWER
- FAULT INDICATION LED PER AMPLIFIEF
- HIGH FFFICIENCY & LOW STANDBY CURRENT
- 100 / 70 / 50 V OLITPLIT

## **OVERVIEW**

D150 and D500 class D transformerless amplifiers provide 100, 70 or 50V audio output for distributed loudspeaker systems. The amplifiers are compatible with the V2000 amplifier mainframe and LSZDC dual line surveillance interface module. The maximum output power is user configurable from 25W to 150W (D150) and from 25W to 500W (D500). Up to 10 D150 and D500 amplifiers modules can be housed within a single V2000 amplifier mainframe.

The configurable output power capability of the D500 and D150 amplifier modules enables very flexible use of the mainframe, with reduced mainframe count, lower quiescent power requirement, and improved environmental performance compared with traditional amplifier designs.







## SPECIFICATION

Quiescent Current Module	16mA
D500 Amplifier Modules	
Amplification	Transformerless Class D
Power output @ 100V	25W to 500W
Power output @ 70V	25W to 350W
Power output @ 50V	25W to 250W
Efficiency	>=83%
Frequency response	100Hz to 20kHz +/- 3dB
THD	< 0.5%
Output Noise85dB (A	A-weighted) below full output
Mechanical	
Module Weight	0.8kg

## **D150 Amplifier Modules (100V Output)**

	. ,
Amplification	Transformer- less Class D
Power output @ 100V	25W to 150W
Power output @ 70V	150W
Power output @ 50V	150W
Efficiency	>=86%
Frequency response	100Hz to 20kHz +/- 3dB
THD	< 0.5%
Output Noise	<85dB below full output
Environmental	
Operating	10°C to +55°C
Storage	20°C to +55°C
Humidity Range	0% to 93% non -condensing
Ingress Protection	IP20 as part of V2000



This equipment is designed and manufactured to conform to the following EC standards:

EMC: EN55103-1/E1, EN55103-2/E5, EN50121-4, ENV50204

Safety: EN60065

Manufacturer

Application Solutions (Safety and Security) Limited
Unit 17 - Cliffe Industrial Estate - Lewes - East Sussex - BN8 6JL - U.K.

Tel: +44(0)1273 405411





Assessed to ISO 9001 LPCB Cert No: C1043

All rights reserved.