

BD 5EN

BIDIRECTIONAL SOUND PROJECTOR



Description

BD 5EN is a weatherproof bidirectional sound projector suitable for all those installations where high intelligibility for alarm messages broadcasting and great sound reproduction quality are required. Thanks to its IP65 protection grade, it can be installed both indoor and outdoor. Moreover, a modern and endearing design makes it the perfect product for environments where projectors are intended also as architectural elements and contribute to improve global aesthetics.

Features

- \rightarrow 2 x 5" fullrange transducers.
- \rightarrow Power selectable (100 V): 20 W 10 W 5 W 2.5 W.
- > 86 dB sensitivity.
- > Colour white RAL 9016.
- > Flameproof ABS body, steel grille.
- > In/out ceramic terminal block.
- > Thermal fuse protection.
- > Protection grade IP65.

Part Number

13133077 BD 5EN

White - RAL 9016 EAN 8024530011130




BD 5EN

BIDIRECTIONAL SOUND PROJECTOR

Line Art 2D





TECHNICAL SPECIFICATIONS

Acoustical specifications

Frequency Response (-10dB) 150 Hz ÷ 18000 Hz

Max SPL @ 1m 99 dB Max SPL @ 4m 87 dB 210° Coverage angle System Sensitivity 86 dB System Sensitivity 1W @ 4m 74 dB Amplification Full Range

Power section

Power Handling 20 W 80 W PEAK Peak Power Handling Protections Thermal fuse

Recommended Amplifiers

DMA 504, DMA 162, DMA 162P, DXT 3000, DXT 4000, DXT 7000

2 x 5.0"

Transducers Fullrange

Input/Output section Input connectors Ceramic screw terminals

> Output connectors Ceramic screw terminals

Constant Voltage Transformer 100 V

Power selection 1 20 W - 500 ohm Power selection 2 10 W - 1000 ohm Power selection 3 5 W - 2000 ohm Power selection 4 2.5 W - 4000 ohm

Standard compliance IP protection grade IP 65

> Safety agency CE compliant

EN54-24 certified Yes

CPR number 0068-CPR-058/2014

Physical specifications Cabinet/Case Material ABS

> Hardware Wall mount metal plate

Grille Steel

White - RAL 9016 Color

Technical Specifications Page 2 of 3



BD 5ENBIDIRECTIONAL SOUND PROJECTOR

Size / Weight |

Height Width Depth Weight 183 mm / 7.2 inches 332 mm / 13.07 inches 176 mm / 6.93 inches 3.59 kg / 7.91 lbs

Technical Specifications Page 3 of 3