


PLP 50EN

CEILING SPEAKER WITH PLASTIC FIRE DOME



Description

PLP 50EN is a ceiling speaker featuring a flameproof plastic back can, designed for recess installation into ceilings or panels. It is especially suitable for broadcasting alarm messages thanks to the highly intelligible sound reproduction and its resistance to high temperatures reached during fires. The terminal connection blocks, for input and output flameproof cables, are made of ceramic material. A thermal fuse protects the integrity of the line in case of heat affecting the speaker. Ground screw available (if needed). Cables inside speaker made using flameproof leads.

Features

- > 5" fullrange transducer.
- \rightarrow Power selectable (100 V): 6 W 3 W 1.5 W.
- > 93 dB sensitivity.
- > Colour white RAL 9016.
- > Plastic frame and back can, steel grille.
- > In/out ceramic terminal block.
- > Thermal fuse protection.

Part Number

13100008 PLP 50EN


White - RAL 9016 EAN 8024530014391




PLP 50EN

CEILING SPEAKER WITH PLASTIC FIRE DOME

Line Art 2D





TECHNICAL SPECIFICATIONS

Acoustical specifications Frequency Response (-10dB) 130 Hz ÷ 15000 Hz

Max SPL @ 1m 101 dB Max SPL @ 4m 89 dB 165° Coverage angle System Sensitivity 93 dB System Sensitivity 1W @ 4m 81 dB

Power section **Amplification** Full Range

Power Handling 6 W 24 W PEAK Peak Power Handling Protections Thermal fuse

Recommended Amplifiers DXT 3000, DXT 4000, DXT 7000

Transducers Fullrange 1 x 5.0"

Input/Output section Input connectors Ceramic screw terminals

Output connectors Ceramic screw terminals

Constant Voltage Transformer 100 V

Power selection 1 6 W - 1667 ohm Power selection 2 3 W - 3333 ohm Power selection 3 1.5 W - 6667 ohm

Standard compliance Safety agency CE compliant

> EN54-24 certified Yes

CPR number 0068-CPR-051/2017

Physical specifications Cabinet/Case Material Plastic

> Hardware Plastic back cover

Grille Steel

White - RAL 9016 Color Size / Weight Depth 71 mm / 2.8 inches

66 mm / 2.6 inches Recessed Depth 175 mm / 6.89 inches Diameter Cut out diameter 149 mm / 5.87 inches Weight 0.66 kg / 1.46 lbs

Technical Specifications Page 2 of 3



PLP 50EN

CEILING SPEAKER WITH PLASTIC FIRE DOME

Technical Specifications Page 3 of 3