



Description

HD 21EN is a plastic horn speaker suitable for broadcasting alarm messages thanks to the highly intelligible sound reproduction and its environmenal resistance. The terminal connection blocks, for input and output flameproof cables, are made of ceramic material. A thermal fuse protects the integrity of the line in case of heat affecting the speaker. It can be easily aimed towards any direction through the adjustable wall-mount bracket, and thanks to its IP66 protection grade it can be installed both indoor and outdoor.

Features

- > 1.5" compression driver.
- \rightarrow Power selectable (100 V): 30 W 15 W 7.5 W 3.75 W.
- > 104 dB sensitivity.
- > Colour grey RAL 7035.
- > Plastic body.
- > In/out ceramic terminal block.
- > Thermal fuse protection.
- > Protection grade IP66.


Part Number


13133075 HD 21EN

Grey - RAL 7035 EAN 8024530010461



Line Art 2D





TECHNICAL SPECIFICATIONS

Acoustical specifications

Frequency Response (-10dB) 340 Hz ÷ 9000 Hz

Max SPL @ 1m117 dBMax SPL @ 4m105 dBCoverage angle135°System Sensitivity104 dBSystem Sensitivity 1W @ 4m92 dB

Power sectionPower Handling30 WPeak Power Handling120 W PEAK

Protections Thermal fuse
Recommended Amplifiers DXT 3000, DXT 4000, DXT 7000

Transducers Compression Driver 1 x 1.5"

Input/Output section | Input connectors | Ceramic screw terminals |

Output connectors Ceramic screw terminals
Constant Voltage Transformer 100 V

Constant Voltage Transformer

Power selection 1

Power selection 2

Power selection 3

Power selection 4

100 V

30 W - 333 ohm

15 W - 667 ohm

7.5 W - 1333 ohm

3.75 W - 2667 ohm

Standard compliance | IP protection grade | IP 66

Safety agency CE compliant

EN54-24 certified Ye

CPR number 1488-CPR-0652/W

Physical specifications | Cabinet/Case Material ABS

Hardware Stainless steel bracket
Color Grey - RAL 7035
Height 212 mm / 8.35 inches
Depth 280 mm / 11 02 inches

 Size / Weight
 Height
 212 mm / 8.35 inches

 Depth
 280 mm / 11.02 inches

 Weight
 2.1 kg / 4.63 lbs

Technical Specifications Page 2 of 2